



The new *DuraLite PLR* series of self-retracting lifelines is built around a rugged alloy-steel, load-bearing chasis which contains a modular composite drum, a sealed brake assembly and dual pawls crafted from state-of-the-art aluminum alloy. The composite housing is durable and works in concert with the internal components to make this one of the most light-weight, full-featured SRL's available.

As with all *FallTech* SRL's, arrest forces are kept to 900 lbs. or less and deceleration distances are considerably below the allowable limit of 54". Additionally, the alloy steel Z359-compliant load-indicating swivel carabiner is standard equipment at the attachment end. *DuraLite PLR* meets or exceeds the requirements of OSHA 1926 and ANSI Z359.1-2007.



DuraLite PLR Cable SRL

- 3/16" Stainless Steel Cable
- Maximum Weight of 17 lbs.

727730: 30' Cable SRL
727740: 40' Cable SRL
727750: 50' Cable SRL
727760: 60' Cable SRL

DuraLite PLR Web SRL

- 1" Polyester Webbing
- Maximum Weight of 13 lbs.

727730W: 30' Web SRL
727740W: 40' Web SRL

DuraLite PLR Rope SRL

- 3/16" Aramid Fiber Rope
- Synthetic Fiber Rope Resists Abrasion, Heat and Electrical Conductivity
- Maximum Weight of 14 lbs.

727730R: 30' Rope SRL
727740R: 40' Rope SRL
727750R: 50' Rope SRL
727760R: 60' Rope SRL