



OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

Frequency of inspection in the following categories:

General Industry: _____ Construction: _____

Your Organization: _____ Manufacturer: _____

Manufacturer of equipment:

Name of Manufacturer: _____

Serial #: _____ Model #: _____

Date of Manufacture: ____/____/____

Inspection:

Date: ____/____/____

Name of competent person:

Name of user (authorized person):



LOOK AT: **1** HARDWARE **2** WEBBING
3 STITCHING **4** LABELS/TAGS

| 1 | HARDWARE | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|---|-----------------|-------------------------------------|--------------------------|
| | Rust/corrosion | | |
| | Deformed/bent | | |
| | Burrs/cracks | | |
| | Weld spots/slag | | |
| | Missing rivets | | |
| | Springs | | |
| | Functionality | | |
| | Other | | |

| 2 | WEBBING | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|---|---------------------|-------------------------------------|--------------------------|
| | Cuts/burns/holes | | |
| | Excessive wear | | |
| | Excessive UV damage | | |
| | Chemical attack | | |
| | Other | | |

| 3 | STITCHING | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|---|-----------|-------------------------------------|--------------------------|
| | Missing | | |
| | Loose | | |
| | Broken | | |
| | Other | | |

| 4 | LABELS/TAGS | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|---|-------------|-------------------------------------|--------------------------|
| | Missing | | |
| | Illegible | | |
| | Dates | | |
| | Other | | |

*See user instruction manual for complete inspection procedures and requirements.