

INSPECTION FORM:

Cable Lanyard



OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

- LOOK AT: **1** HARDWARE **2** CABLE **3** WEBBING **4** STITCHING **5** LABELS/TAGS
- PASS FAIL

Frequency of inspection in the following categories:

General Industry: _____ Construction: _____

Your Organization: _____ Manufacturer: _____

Manufacturer of equipment:

Name of Manufacturer: _____

Serial #: _____ Model #: _____

Date of Manufacture: ____/____/____

Inspection: Remove from service when:

Date: ____/____/____ Date: ____/____/____

Name of competent person:

Name of user (authorized person):



2	CABLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Rust/corrosion		
	Chemical damage		
	Birdcaging		
	Broken wire strands		
	Links/bent strands		
3	WEBBING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Cuts/burns/holes		
	Excessive wear		
	Excessive UV damage		
	Chemical attack		
	Other		
4	STITCHING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Missing		
	Loose		
	Broken		
	Other		
5	LABELS/TAGS	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Missing		
	Illegible		
	Dates		
	Other		

*See user instruction manual for complete inspection procedures and requirements.