

# INSPECTION FORM:

# Cable Lanyard



## OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



## 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

### Frequency of inspection in the following categories:

General Industry: \_\_\_\_\_ Construction: \_\_\_\_\_

Your Organization: \_\_\_\_\_ Manufacturer: \_\_\_\_\_

### Manufacturer of equipment:

Name of Manufacturer: \_\_\_\_\_

Serial #: \_\_\_\_\_ Model #: \_\_\_\_\_

Date of Manufacture: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Inspection:

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Remove from service when:

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Name of competent person:

\_\_\_\_\_

### Name of user (authorized person):

\_\_\_\_\_



LOOK AT: **1** HARDWARE **2** CABLE  
**3** WEBBING **4** STITCHING  
**5** LABELS/TAGS  PASS  FAIL

1	HARDWARE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Rust/corrosion		
	Deformed/bent		
	Burrs/cracks		
	Weld spots/slag		
	Missing rivets		
	Springs		
	Functionality		
	Other		

2	CABLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Rust/corrosion		
	Chemical damage		
	Birdcaging		
	Broken wire strands		
	Links/bent strands		

3	WEBBING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Cuts/burns/holes		
	Excessive wear		
	Excessive UV damage		
	Chemical attack		
	Other		

4	STITCHING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Missing		
	Loose		
	Broken		
	Other		

5	LABELS/TAGS	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Missing		
	Illegible		
	Dates		
	Other		

\*See user instruction manual for complete inspection procedures and requirements.