

## **Inspection Form: Full-Body Harness**

Inspection:		Frequency of Inspection in the Following Categories:			
Date:// Name of Competent Person:		General Industry:		Construction:	
		Your Organization:		Manufacturer:	
		Manufacturer of Equipment:			
Name of User (Authorized Person):		Name of Manufacturer:			
		Serial #: Model #:			
		Date of Manufacture:/			
Checklist					
LOOK AT:					
1 HARDWARE 2 WEBBING	3 STITCHING 4 LABELS/TA	AGS		<b>✓</b> PASS	X FAIL
1 HARDWARE 🗸 🕽	2 WEBBING	X STITCHING	✓ X	4 LABELS / TAGS	✓ X
Rust / Corrosion	Cuts / Burns / Holes	Missing		Missing	
Deformed / Bent	Excessive Wear	Loose		Illegible	
Burrs / Cracks	Excessive UV Damage	Broken		Dates	
Weld Spots / Slag	Chemical Attack	Other		Other	
MIssing Rivets	Other				
Springs					
Functionality					
runctionality					



## OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



## 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a Competent Person other than the user at intervals of no more than one year.

 ${}^{*}$ See user instruction manual for complete inspection procedures and requirements.