

# Inspection Form: Lanyard (Webbing)

## Inspection:

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

## Name of Competent Person:

\_\_\_\_\_

## Name of User (Authorized Person):

\_\_\_\_\_

## Frequency of Inspection in the Following Categories:

General Industry: \_\_\_\_\_ Construction: \_\_\_\_\_

Your Organization: \_\_\_\_\_ Manufacturer: \_\_\_\_\_

## Manufacturer of Equipment:

Name of Manufacturer: \_\_\_\_\_

Serial #: \_\_\_\_\_ Model #: \_\_\_\_\_

Date of Manufacture: \_\_\_\_/\_\_\_\_/\_\_\_\_

# Checklist

## LOOK AT:

1	HARDWARE	2	WEBBING	3	STITCHING	4	LABELS / TAGS
	<input checked="" type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/>
	Rust / Corrosion		Cuts / Burns / Holes		Missing		Missing
	Deformed / Bent		Excessive Wear		Loose		Illegible
	Burrs / Cracks		Excessive UV Damage		Broken		Dates
	Weld Spots / Slag		Chemical Attack		Other		Other
	Missing Rivets		Other				
	Springs						
	Functionality						
	Other						



### OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



### 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a Competent Person other than the user at intervals of no more than one year.

\*See user instruction manual for complete inspection procedures and requirements.