INSPECTION FORM:

Self-Retracting Lifeline



OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

_	<i>c</i> •			e	•		•
Frequency	v ot incr	ACTION I	ın tha	TALLA	wina	Cate	10riac:
i iequelic	y OI 11136	C CUOIII			44 II IQ	Cate	401 I C 3.

Name of user (authoriz	zed person):			
Name of competent person:				
Date:/	Date:/			
Inspection:	Remove from service when:			
Date of Manufacture:/_	/			
Serial #:	Model #:			
Name of Manufacturer:				
Manufacturer of equip	ment:			
Your Organization:	Manufacturer:			
General Industry:	Construction:			



LOOK AT:

1 HARDWARE

2 WEBBING

3 STITCHING

4 LABELS/TAGS

1	HARDWARE	$\overline{\checkmark}$	X
Rust/c	Rust/corrosion		
Deform	ned/bent		
Burrs/	Burrs/cracks		
Weld s	Weld spots/slag		
Missin	Missing rivets		
Spring	Springs		
Functi	Functionality		-
Other			

2	WEBBING	\checkmark	X
Cuts/burns/holes			
Excessive wear			
Excessive UV damage			
Chemical attack			
Other			

3	STITCHING	V	X
Missing			
Loose			
Broken			
Other			

4	LABELS/TAGS	$\overline{\checkmark}$	X
Missin	g		
Illegibl	Illegible		
Dates			
Other			







^{*}See user instruction manual for complete inspection procedures and requirements.